



• S P E C I F I C A T I O N S •

VAULT BODY . . . . . TWO 1/2" STEEL PLATES WELDED TO FORM THE VAULT SIDE WALLS, BACK AND TOP WITH SPACE BETWEEN PLATES CONCRETE FILLED.

DOOR . . . . . 3 1/2" VAULT DOOR WITH (2) 4-TUMBLER KEY CHANGING, BANK TYPE COMBINATION LOCKS WITH SHIELDED DIALS.

TIMELOCK . . . . . 3-MOVEMENT TIMELOCK FURNISHED AS STANDARD EQUIPMENT.

ALARM SYSTEM . . . . . VAULT DESIGNED TO RECEIVE TWO SOUND WAVE RECEIVERS, (2) THERMOS ON BACK OF DOOR + DOOR CONTACT. FURNISHED ONLY WHEN SPECIFIED. (OPTIONAL EXTRA)

ELECTRICAL . . . . . TWO FLUORESCENT LIGHTS MOUNTED ON CEILING OF VAULT IN FULL WIDTH FIXTURE. CONDUIT STUBS OUT PROVIDED.

INSTALLATION . . . . . DOOR + FRAME CAN BE REMOVED FROM VAULT STRUCTURE TO REDUCE THE OVERALL DEPTH OF THE UNIT TO 32 1/4". FOUR HOLES PROVIDED IN BOTTOM PLATE FOR SECURING UNIT.

SECURITY . . . . . MEETS INSURANCE RATING BOARD SPECIFICATIONS CLASS 6B VAULT

FINISH . . . . . VAULT EXTERIOR + INTERIOR PRIME PAINTED. FINISH COLOR AFTER INSTALLATION (NOT BY DIEBOLD). TRIM FRAME, DOOR FRONT, HINGE COVERS, + BOLTWORK COVER IS STAINLESS STEEL. DOOR EDGE + JAMBS ARE POLISHED STEEL.

WEIGHT OF UNIT . . . . . APPROXIMATELY 10,000 LBS. CRATED 10,500

OPTIONAL FEATURES + INTERIOR QUESTIONNAIRE

- RIGHT SWING VAULT DOOR       LEFT SWING VAULT DOOR
- ALARM EQUIPMENT (FOR CONNECTION TO BANKS PRESENT ALARM SYSTEM)
- ALARM EQUIPMENT (NEW #16-16 OR #115-35) CONTROL CABINET IN SECURITY HOUSING.

CONSTRUCTION + THICKNESS OF FLOOR TO SUPPORT VAULT IS \_\_\_\_\_  
 (VAULT MUST BE BOLTED TO CONCRETE FLOOR TO RECEIVE ALARM CERTIFICATE)

