

## Technical Data Sheet

## SAFE RANGE S.A.B.S. CATEGORY III

The main feature of the Giant Category III range of Safes is the CERASTRA Armour, which is in every way technically superior to the Standard T.D.R. protection currently available.

The major markets for this range embrace the financial institutions, jewellery and bullion industry as well as large Government and commercial outlets.

## **SPECIFICATION**

Armour Type: CERASTRA Armour (Patent pending) 100 mm thickness.

Resistance to attack: Subject to C.S.I.R. report No. ME1615/1 (Test thickness 100 mm) 8th May 1979 available on request.

Oxy-arc Drill Angle G Dimensi	ons:					Not po	hours
	TYPE	3225	3429	3929	4429	5629	6529
OUTSIDE	Height mm Width mm Depth mm	825 650 735	875 750 810	1000 750 810	1130 750 810	1445 750 810	1690 750 810
INSIDE	Height mm Width mm Depth mm	570 395 395	620 495 470	750 495 470	875 495 470	1180 495 470	1410 495 470
MASS kg		890	1100	1300	1540	1660	2200

Locking Mechanism: 1 Four Wheel combination lock is fitted capable of 108 combinations. Giant Security has developed an electronic combination lock as an optional extra.

In addition two high precision 8 lever key locks are fitted.
All locks are protected by unique relocking devices which automatically deadlock the boltwork if the lock is attacked by explosives.

Boltwork: The door is secured and controlled by hardchrome plated bolts 45 mm diameter.

Internal Fittings: Type 3225, 3429

3929 4429, 5629 6529 1 adjustable shelf & 2 drawers 2 adjustable shelves & 2 drawers 3 adjustable shelves & 2 drawers 4 adjustable shelves & 2 drawers

